

Productname : SOLVENT 50  
Ref.Nr.: BDS001046\_3\_20111220

Creationdate : 20.12.11 Version : 1.0  
Replaces: AB28100

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**SOLVENT 50**  
Aerosol

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Cleaners - Precision

**1.3. Details of the supplier of the safety data sheet**

**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele  
Belgium  
Tel.: +32(0)52/45.60.11  
Fax.: +32(0)52/45.00.34  
E-mail : hse@crcind.com

Subsidiaries		Tel	Fax
CRC Industries Finland Oy	Asemanrinne 13, 08500 Lohja	+358/(19)32.921	+358/(19)383.676
CRC Industries France	6, avenue du marais, B.P. 90028, 95102 Argenteuil Cedex	01.34.11.20.00	01.34.11.09.96
CRC Industries Deutschland GmbH	Südring 9, D-76473 Iffezheim	(07229) 303.0	(07229)30 32 66
CRC INDUSTRIES IBERIA S.L.U.	GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTRI. DE HONTORIA, 40195 SEGOVIA	0034/921.427.546	0034/921.436.270
CRC Industries Sweden	Kryptogatan 14, 431 53 Mölndal	0046/31 706 84 80	0046/31 27 39 91

**1.4. Emergency telephone number**

CRC Industries Europe, Belgium: Tel.: +32(0)52/45.60.11 (office hours)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to 67/548/EEC or 1999/45/EC:**

**Health:** R38: Irritating to skin.



**CRC Industries Europe bvba**

Touwslagerstraat 1, 9240 Zele – Belgium  
Tel (+32) (0) 52 / 45 60 11 – Fax (+32) (0) 52 / 45 00 34 – www.crcind.com

1 / 10

<b>Productname :</b>	SOLVENT 50	<b>Creationdate :</b>	20.12.11 Version : 1.0
<b>Ref.Nr.:</b>	BDS001046_3_20111220	<b>Replaces:</b>	AB28100

<b>Physical:</b>	R43: May cause sensitization by skin contact. R67: Vapours may cause drowsiness and dizziness. EXTREMELY FLAMMABLE
<b>Environment:</b>	R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 2.2. Label elements

Contains:

Orange, sweet, ext.

**Warning symbol(s) :**

EXTREMELY FLAMMABLE



Xi : IRRITANT



N : DANGEROUS FOR THE ENVIRONMENT



**Risk-phrase(s) :**

R38: Irritating to skin.  
R43: May cause sensitization by skin contact.  
R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R67: Vapours may cause drowsiness and dizziness.

**Safety-phrase(s) :**

S2: Keep out of the reach of children.  
S16: Keep away from sources of ignition - No smoking.  
S23: Do not breathe vapours/spray.  
S24: Avoid contact with skin.  
S35: This material and its container must be disposed of in a safe way.  
S37: Wear suitable gloves.  
S51: Use only in well-ventilated areas.

**Extra label elements according to Aerosol Dispenser Directive 75/324/EC:**

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Without adequate ventilation formation of explosive mixtures may be possible.

**Other extra label elements:**

Remark: Preparations classified as harmful on the basis of an aspiration hazard need not be labelled as harmful with R65 when placed on the market in aerosol containers or in containers fitted with a sealed spray attachment. (EU-Directive 67/548 Annex VI 9.4)

## 2.3. Other hazards

None

<b>Productname :</b>	SOLVENT 50	<b>Creationdate :</b>	20.12.11 Version : 1.0
<b>Ref.Nr.:</b>	BDS001046_3_20111220	<b>Replaces:</b>	AB28100

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable.

#### 3.2. Mixtures

Hazardous ingredient	CAS-nr.	EC-nr	w/w %	symbol	R-phrases*	Notes
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	-	921-024-6	25-50	F,Xn,N	11-38-51/53-65-67	
cyclohexane	110-82-7	203-806-2	10-25	F,Xn,N	11-38-50/53-65-67	A
Orange, sweet, extract	8028-48-6	232-433-8	10-25	Xn,N	10-38-43-50/53-65	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	-	919-857-5	10-25	Xn	10-65-66-67	
carbon dioxide	124-38-9	204-696-9	1-5	-	-	A,G

**Explanation notes**

A : substance with Community workplace exposure limit

G : exempted from the obligation to register in accordance with art.2(7)(a) of REACH Regulation No 1907/2006

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	01-2119475514-35	-	921-024-6	25-50	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2	H225, H315, H336, H304, H411	
cyclohexane	01-2119463273-41	110-82-7	203-806-2	10-25	Flam. Liq. 2, Asp. Tox. 1, Skin Irrit. 2, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1	H225, H304, H315, H336, H400, H410	A
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	01-2119463258-33	-	919-857-5	10-25	Flam. Liq. 3, Asp. Tox. 1, STOT SE 3	H226, H304, H336	
carbon dioxide		124-38-9	204-696-9	1-5	Press. Gas	H280	A,G

**Explanation notes**

A : substance with Community workplace exposure limit

G : exempted from the obligation to register in accordance with art.2(7)(a) of REACH Regulation No 1907/2006

(\* Explanation phrases : see chapter 16)

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

**Contact with eyes :** If substance has got into eyes, immediately wash out with plenty of water  
Seek medical advice

**Contact with skin :** Remove contaminated clothing immediately and drench affected skin with



<b>Productname :</b>	SOLVENT 50	<b>Creationdate :</b>	20.12.11 Version : 1.0
<b>Ref.Nr.:</b>	BDS001046_3_20111220	<b>Replaces:</b>	AB28100

	plenty of water. Then wash with soap and water Seek medical advice
<b>Inhalation :</b>	Fresh air, keep warm and at rest. Seek medical attention if ill effects occur
<b>Ingestion :</b>	Ingestion is unlikely to occur If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>Inhalation :</b>	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
<b>Ingestion :</b>	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms : sore throat, abdominal pain, nausea, vomiting
<b>Skin contact :</b>	Irritating to skin May cause sensitisation by skin contact. Symptoms : redness and pain
<b>Eye contact :</b>	May cause irritation. Symptoms : redness and pain

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>General Advice :</b>	If you feel unwell, seek medical advice (show the label where possible) If symptoms persist always call a doctor
-------------------------	---

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

foam, carbon dioxide or dry agent

#### 5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C  
Forms hazardous decomposition products  
CO,CO2

#### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water  
In case of fire, do not breathe fumes

### SECTION 6: Accidental release measures



<b>Productname :</b>	SOLVENT 50	<b>Creationdate :</b>	20.12.11 Version : 1.0
<b>Ref.Nr.:</b>	BDS001046_3_20111220	<b>Replaces:</b>	AB28100

**6.1. Personal precautions, protective equipment and emergency procedures**

Shut off all ignition sources  
Ensure adequate ventilation  
Wear suitable protective clothing and gloves.

**6.2. Environmental precautions**

Do not allow to enter public sewers and watercourses

**6.3. Methods and material for containment and cleaning up**

Absorb spillage in suitable inert material

**6.4. Reference to other sections**

For further information see section 8

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Keep away from heat and sources of ignition  
Take precautionary measures against static discharges  
Equipment should be earthed  
Use explosion-proof electrical/ventilating/lighting/?/equipment.  
Use only non-sparking tools.  
Do not breathe aerosols or vapours.  
Ensure adequate ventilation  
Avoid contact with skin and eyes.  
Wash thoroughly after use  
Wear protective gloves/protective clothing/eye protection/face protection.

**7.2. Conditions for safe storage, including any incompatibilities**

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.  
Keep out of reach of children.

**7.3. Specific end use(s)**

Cleaners - Precision

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

<b>Productname :</b>	SOLVENT 50	<b>Creationdate :</b>	20.12.11 Version : 1.0
<b>Ref.Nr.:</b>	BDS001046_3_20111220	<b>Replaces:</b>	AB28100

**Exposure limits :**

Hazardous ingredient	CAS-nr.	method	
<b>EU established exposure limits:</b>			
cyclohexane	110-82-7	TWA	200 ppm
carbon dioxide	124-38-9	TWA	5000 ppm
<b>National established exposure limits, United Kingdom</b>			
cyclohexane	110-82-7	TWA	100 ppm
		STEL	300 ppm
carbon dioxide	124-38-9	TWA	5000 ppm
		STEL	15000 ppm

**8.2. Exposure controls**

<b>Control procedures :</b>	Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges
<b>Personal protection :</b>	Take precautions to avoid contact with skin and eyes when handling the product. Ensure adequate ventilation
<b>inhalation :</b>	In case of insufficient ventilation, wear suitable respiratory equipment. Air purifying respirator equipped with organic gas/vapor cartridge (type A or AX)
<b>hands and skin :</b>	Wear suitable protective gloves (nitrile)
<b>eyes :</b>	Wear safety goggles.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

(for aerosols data for the product without propellant)

<b>Apperance : physical state :</b>	Liquid.
<b>colour :</b>	Colourless to yellow.
<b>odour :</b>	Citrus.
<b>pH :</b>	Not applicable.
<b>Boiling point/range :</b>	55-190
<b>Flash point :</b>	< 0 °C
<b>Explosion limits : upper limit :</b>	Not available.
<b>lower limit :</b>	Not available.
<b>Vapour pressure :</b>	Not available.
<b>Relative density :</b>	0.753 g/cm <sup>3</sup> (@ 20°C).
<b>Solubility in water :</b>	Insoluble in water
<b>Auto-ignition :</b>	> 200 °C



<b>Productname :</b>	SOLVENT 50	<b>Creationdate :</b>	20.12.11 Version : 1.0
<b>Ref.Nr.:</b>	BDS001046_3_20111220	<b>Replaces:</b>	AB28100

**9.2. Other information**

VOC: 722 g/l

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No hazardous reactions known if used for its intended purpose

**10.2. Chemical stability**

Stable

**10.3. Possibility of hazardous reactions**

No hazardous reactions known if used for its intended purpose

**10.4. Conditions to avoid**

Avoid overheating

**10.5. Incompatible materials**

Strong oxidising agent

**10.6. Hazardous decomposition products**

CO,CO2

**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

<b>Inhalation :</b>	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
<b>Ingestion :</b>	After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.
<b>Skin contact :</b>	May cause sensitisation by skin contact. Irritating to skin
<b>Eye contact :</b>	May cause irritation.

**Toxicological data :**

**Productname :** SOLVENT 50  
**Ref.Nr.:** BDS001046\_3\_20111220

**Creationdate :** 20.12.11 Version : 1.0  
**Replaces:** AB28100

Hazardous ingredient	CAS-nr.	method	
cyclohexane	110-82-7	LD50 oral rat	> 5000 mg/kg

## SECTION 12: Ecological information

### 12.1. Toxicity

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
cyclohexane	110-82-7	EC50 daphnia	0.9 mg/l

### 12.2. Persistence and degradability

No experimental data available

### 12.3. Bioaccumulative potential

No experimental data available

### 12.4. Mobility in soil

Insoluble in water

### 12.5. Results of PBT and vPvB assessment

No information available

### 12.6. Other adverse effects

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Product :** This material and its container must be disposed of in a safe way. Do not discharge into drains or the environment, dispose to an authorised waste collection point.  
**Contaminated packaging :** Disposal should be in accordance with local, state or national legislation



Productname :	SOLVENT 50	Creationdate :	20.12.11 Version : 1.0
Ref.Nr.:	BDS001046_3_20111220	Replaces:	AB28100

**SECTION 14: Transport information****14.1. UN number**

UN-number : 1950

**14.2. UN proper shipping name**

Proper shipping name: AEROSOLS, flammable(naphta, cyclohexane)

**14.3. Transport hazard class(es)**Class: 2.1  
ADR/RID - Classification code: 5F**14.4. Packing group**

Packing group: Not applicable.

**14.5. Environmental hazards**ADR/RID - Environmentally  
hazardous: Yes  
IMDG - Marine pollutant: Marine pollutant  
IATA/ICAO - Environmentally  
hazardous: Yes**14.6. Special precautions for user**ADR/RID - Tunnelcode: (D)  
IMDG - Ems: F-D,S-U  
IATA/ICAO - PAX: 203  
IATA/ICAO - CAO: 203**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

The Safety Data Sheet is compiled according to the current European requirements.  
Dir. 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.  
EU-directive 99/45/EC



<b>Productname :</b>	SOLVENT 50	<b>Creationdate :</b>	20.12.11 Version : 1.0
<b>Ref.Nr.:</b>	BDS001046_3_20111220	<b>Replaces:</b>	AB28100

Regulation (EC) No 1907/2006 (REACH)

**15.2. Chemical safety assessment**

No information available

**SECTION 16: Other information**

- \*Explanation risk-phrases:
- R10: Flammable.
  - R11: Highly flammable.
  - R38: Irritating to skin.
  - R43: May cause sensitization by skin contact.
  - R65: Harmful: may cause lung damage if swallowed.
  - R66: Repeated exposure may cause skin dryness or cracking.
  - R67: Vapours may cause drowsiness and dizziness.
  - R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
  - R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- \*Explanation hazard statements:
- H225 : Highly flammable liquid and vapour.
  - H226 : Flammable liquid and vapour.
  - H280 : Contains gas under pressure; may explode if heated.
  - H304 : May be fatal if swallowed and enters airways.
  - H315 : Causes skin irritation.
  - H336 : May cause drowsiness or dizziness.
  - H400 : Very toxic to aquatic life.
  - H410 : Very toxic to aquatic life with long lasting effects.
  - H411 : Toxic to aquatic life with long lasting effects.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.